	<u>Yananananananananananananananananananan</u>
Quarter Inch Seam Guide - Cut out this guide. Place needle just inside the Quarter Inch line. ? Edge of paper is 1/4" from the needle.	& Quarter Inch Line

Quarter Inch Seam Practice

- 1. Using paper scissors, cut out the seam guide on the outer lines. Note: this seam guide should be exactly 1" wide. If it is not, do not use it as the guide was distorted during download or copying.
- 2. Position the guide so the sewing machine needle is just inside the Quarter Inch Line and the smaller side of the paper is to the right of the needle.
- 3. Make sure the paper is positioned such that if you were to sew on the line it would feed straight into the machine. Mark or note where the edge of the paper to the right of the needle falls on your machine. This is your scant Quarter Inch seam line.
- 4. Cut three 1-1/2" x 3" pieces of fabric
- 5. Sew the lengths of the three strips of fabric together with a 1/4" seam allowance.
- 6. Press each seam.
- 7. Check that the finished unit measures 3-1/2" x 3". If not, double check seam allowances and pressing. Make corrections before starting to sew your project.

Quarter Inch Seam Guide - Cut out this guide. Place needle just inside the Quarter Inch line. ? Edge of paper is 1/4" from the needle.	€ Quarter Inch Line

Quarter Inch Seam Practice

- 1. Using paper scissors, cut out the seam guide on the outer lines. Note: this seam guide should be exactly 1" wide. If it is not, do not use it as the guide was distorted during download or copying.
- 2. Position the guide so the sewing machine needle is just inside the Quarter Inch Line and the smaller side of the paper is to the right of the needle.
- 3. Make sure the paper is positioned such that if you were to sew on the line it would feed straight into the machine. Mark or note where the edge of the paper to the right of the needle falls on your machine. This is your scant Quarter Inch seam line.
- 4. Cut three 1-1/2" x 3" pieces of fabric
- 5. Sew the lengths of the three strips of fabric together with a 1/4" seam allowance.
- 6. Press each seam.
- 7. Check that the finished unit measures 3-1/2" x 3". If not, double check seam allowances and pressing. Make corrections before starting to sew your project.